



CLARK SUSPENSION




type	suspension					
materials	shade : lamp holder cover : lamp tube : cable : wire:	brass (BR) or powdercoated aluminium (BL/WH) marble / aluminium frosted glass, Ø 2-1/4" / 57 mm aircraft steel cables nylon				
wire length	96" / 2438 mm					
light bulb	AC LED board (included), 27 W (A) AC LED board (included), 68 W (B)					
voltage	120V / 240V					
dimmer	refer to our recommended list of dimmer models					
notes	 must be installed by an electrician additional charges for modifications or for special orders lead time between 8-9 weeks dimensions are approximate and may vary slightly 					







ORDER GUIDE: SKU



brass

black


white



LIGHT BULB & DIMMER SPECIFICATIONS

AC LED BOARD - SIZE A

AC LED BOARD - SIZE B



27 W 100V-120V / 240V 100 Lumens / inches LED 2700K 50 000 H CRI ≥90 2 years warranty 3 SDCM consistency 68 W 100V-120V / 240V 100 Lumens / inches LED 2700K 50 000 H CRI ≥90 2 years warranty 3 SDCM consistency

DIMMER LIST COMPATIBILITY FOR G9 LED BULBS – 120V

The dimming technology offering the best results is ELV (electronic low voltage) dimmers with reverse phase or trailing edge control.

DIMMER BRAND	MODEL NUMBER	MAX LEVEL		FLICKERING	OVERALL QUOTE
LUTRON - MAESTRO	MAELV-600	100%	0%	0%-10%	good
LUTRON - SKYLARK	SELV-300P	100%	0%	no	very good
LUTRON - SKYLARK	SELV-303P	100%	0%	no	very good
LUTRON - SKYLARK	CTELV-303P	100%	0%	no	very good
LUTRON - DIVA	DVELV-300P	100%	0%	no	very good
LEGRAND - ADORNE	TRUE UNIVERSAL	100%	30%	no	good

DIMMER LIST COMPATIBILITY FOR G9 LED BULBS - 230V

DIMMER BRAND	MODEL NUMBER	MAX LEVEL		FLICKERING	OVERALL QUOTE
VARILIGHT	V-PRO	100%	2%	no	very good
LEGRAND - NILOÉ	3 996 35	87%	15%	no	good
NIKO	310-0280X	94%	5%	no	very good
NIKO	310-0190X	100%	1%	no	very good

*Other dimmers can yield good results and we recommand conducting your own test before final installation.