




SAINTE 06

Sainte is a collection about the forces that anchor us, a suspension light in dialogue with gravity. Reimagining the rectangle in layered, colourful glass, Sainte offers an elegant floating mass supported by robust nylon ribbons. Powered by a flat wire embedded in the nylon, these anchors carry a casual, contemporary spirit: an everyday material flirting with its graceful, minimalist centre. The form can suspend from any height, at a specified angle, and in multiples, offering infinite architectures and possibilities. As a collection, it presents a dance of contrasting materials and an equilibrium of opposing powers.


- type:** suspension
- construction:** aluminum polished light block, glass anchors and ceiling anchors
laminated glass body
nylon ribbon
PMMA frosted diffuser
- specifications:** source: LED array, integrated
power consumption: 26.8W
colour temperature 2700K, 3000K, dim to warm.
see order guide
colour rendering index: ≥ 90 CRI
colour consistency: 3 SDCM
expected lifetime: $\geq 50\ 000$ h
- control:** 120-277V: On/Off, 0-10V, Phase Dimming (120V only)
220-240V: On/Off, Phase Dimming (Trailing Edge only)
refer to our recommended list of dimmer models
- ribbon length:** total length 20' / 610 cm, width: 2" / 5 cm
- weight:** 41.8 lb / 18.6 kg
- certifications:**     IP20
- warranty:** 2 years




*dimensions are approximate and may vary slightly

ORDER GUIDE: SKU

COLLECTION	MODEL	GLASS BODY (Side A and Side B)	
STE	sainte	06	YEFY yellow, frosted yellow
			LGLG laminated green, laminated green
			MDMD medium grey, medium grey
			DRFB dark red, frosted blush
			LPFS light peach, frosted sand
			*CC custom colour
STE	06	YEFY	



NYLON RIBBON	CANOPY	COLOUR TEMPERATURE (CCT)	CONTROL
BK black	BK black	WL warm light (2700K)	ZT 0-10V dimming
	WH white	NL neutral light (3000K)	PH phase dimming
		D27 dim to warm (2700K to 2200K)	
		D30 dim to warm (3000K to 2200K)	
		CCT Other CCT available upon request*	
BK	BK	WL	ZT



Top and bottom of glass are always ultraclear and not available in color

ZT = STE06YEFYBKWKWLZT
example

*Specific CCT selection only available in 100K increments, from 2200K to 4000K inclusively. Not available with Dim-to-Warm feature.


GLASS BODY (*Custom colours available upon request)



NYLON RIBBON




MOUNTING OPTIONS



Must be installed at 20 degrees or less.

EU ENERGY LABEL



NOTES:

- must be installed by an electrician
- LED may only be changed by Lambert & Fils or other authorized personnel
- not protected against liquids (refer to IP20)
- additional charges for modifications or for special orders
- please refer to maintenance sheet on website for cleaning instructions