

Isle 15








ISLE 15 - COLOUR PALETTE 1

ISL01B: Guatemala Green + Polished Aluminum

ISL03B: Black Marquina + Polished Aluminum + Guatemala Green + Polished Aluminum

An ode to quiet strength, Isle is a play both on illusion and perception allowing lightness to anchor and foundations to rise. Composed of a delicate glass tube resting on solid-stone and aluminum pedestals and suspended in mid-air like a surreal bridge, Isle is minimal, but never simplistic.



TYPE	Suspension
CONSTRUCTION	Frosted glass tube Polished aluminum or marble block Polished aluminum endcap, canopy and anchors Polyester cord
SPECIFICATIONS	Power consumption: 52W Colour temperature: 3000K 2700K dim to warm 3000K to 2200K dim to warm 2700K to 2200K Colour rendering index: ≥90 CRI Colour consistency: 3 SDCM Expected lifetime: ≥50 000h
CONTROL	120/277V on/off, 0-10V, or phase dimming 220-240V: On/Off, Phase Dimming, DALI Refer to our recommended list of dimmer models on page 6
CORD LENGTH	Mains/line cord- 120" / 304 cm Non-electrical cord- 96" / 244 cm
WEIGHT	ISL01B- 12lb / 5.4Kg ISL03B- 20.5lb / 9.3Kg
CERTIFICATIONS	     IP20
WARRANTY	2 years

NOTES


- Luminaire total height (ceiling to lowest point of luminaire)
Min - 29"/74 cm
Max - 119"/302 cm
- If the position of the canopy is different from the proposed installation. Ceiling anchors can be used as junction boxes for daisy chain.

Contact Lambert et Fils:


- For any height outside standard parameters.
- For installation on slanted ceiling.
- For daisy chain installation.





SM- Surface mounted



DC- Daisy chain



RM-Remote driver



*housing not necessary for
Phase Dimming 220-240VAC
(only driver provided)


REMOTE DRIVER HOUSING

Must be accessible for maintenance in a well aerated location for heat dissipation


Use the following chart to determine proper wiring gauge according to the distance to its location.

GAUGE	MAX ALLOWABLE DISTANCE
18AWG (0.75mm ²)	85 ft. / (26 m)
16AWG (1.5mm ²)	136 ft. / (41 m)
14AWG (2.5mm ²)	216 ft. / (66 m)
12AWG (4mm ²)	343 ft. / (105 m)


MATERIAL*




AL
Polished
aluminum




BM
Black
Marquina
marble




GU
Guatemala
Green
marble



PI
Pink
Portugal
marble



RL
Red
Levanto
marble



RN
Red
Negrais
marble


CORD




BK
Black

MOUNTING


SM
Surface mounted



DC
Daisy chain




RM
Remote Driver



NOTES

- Must be installed by an electrician
- LED may only be changed by Lambert & Fils or other authorized personnel
- Not protected against liquids (refer to IP20)
- Additional charges for modifications or for special orders
- Please refer to maintenance sheet on our website for cleaning instructions
- *All marble colours and vein patterns are unique to each block

LAMP ANATOMY



		Example	Fill with your selection
COLLECTION	ISL Isle	ISL	ISL
MODEL	15	15	15
MATERIAL (Electrical block always polished aluminum)	P1 ISL01B - Guatemala Green (M1) + Polished Aluminum (M2) ISL03B - Black Marquina (M3) + Polished Aluminum (M4) + Guatemala Green (M5) + Polished Aluminum (M6) P2 ISL01B - Polished Aluminum (M1) + Guatemala Green (M2) ISL03B - Black Marquina (M3) + Polished Aluminum (M4) + Red Negrais (M5) + Guatemala Green (M6) P3 ISL01B - Red Levanto (M1) + Red Negrais (M2) ISL03B - Pink Portugal (M3) + Red Levanto (M4) + Pink Portugal (M5) + Red Negrais (M6) P4 ISL01B - Polished Aluminum (M1) + Pink Portugal (M2) ISL03B - Red Levanto (M3) + Polished Aluminum (M4) + Red Levanto (M5) + Pink Portugal (M6) AL All models Polished Aluminum ISL01B - Polished Aluminum (M1, M2) ISL03B - Polished Aluminum (M3, M4,M5)	P1	
CORD	BK Black	BK	BK
CANOPY AND ANCHORS	AL Polished aluminum	AL	AL
MOUNTING	SM Surface mounted RM Remote driver DC Daisy chain	SM	
COLOUR TEMPERATURE (CCT)	WL Warm light (2700K) NL Neutral light (3000K) D27 Dim to warm (2700K-2200K) D30 Dim to warm (3000K-2200K) CCT Other CCT available upon request*	WL	
DIMMING	ZT 0-10V (120VAC only) PH Phase dimming DA DALI (220-240VAC only)	ZT	
FULL SKU		ISL15P1BKALSMWLZT	
		NOTES	

*Specific CCT selection only available in 100k increments, from 2200K to 4000K
inclusively and not available with Dim-to-Warm feature.

TESTED DIMMER COMPATIBILITY LIST - 120V

Compatible with Trailing Edge dimming (Reverse Phase/ELV) or Leading Edge (Forward Phase) dimming.
We strongly recommend using dimmers that require a Neutral wire connection.

DIMMER BRAND	MODEL	MAX LEVEL	MIN LEVEL	DIMMING PROTOCOL
Lutron Diva	DVELV-300P	100%	1%	Phase Cut
Lutron Diva	DVELV-303P	100%	1%	Phase Cut
Lutron Diva	DVRP-253P	100%	1%	Phase Cut
Lutron Skylark	CTELV-303P	100%	1%	Phase Cut
Lutron Skylark	SELV-300P	100%	1%	Phase Cut
Lutron Skylark	SELV-303P	100%	1%	Phase Cut
Lutron Skylark	CTRP-253P	100%	1%	Phase Cut
Lutron Maestro	MA-PRO	100%	1%	Phase Cut
Lutron Caseta	PD-5NE	100%	1%	Phase Cut
Lutron Nova	NTELV-300	100%	1%	Phase Cut

Some dimmers require a minimum load, check specifications.

We recommend conducting your own test before final installation.